

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application:

LISTING OF CLAIMS:

1. (currently amended): An apparatus for adjusting ambient air temperature, comprising:
 - a single base unit, configured to receive an input airflow at said ambient air temperature and generate a base unit output airflow;
 - a first attachment unit, attachable to said single base unit and configured to receive said base unit output airflow and generate a heated output airflow; and
 - a second attachment unit, attachable to said single base unit and configured to receive said base unit output airflow and output ~~a~~ an evaporatively cooled output airflow generated in the single base unit.
2. (original): The apparatus of claim 1, said single base unit comprising:
 - a blower that operates in accordance with a motor.
3. (original): The apparatus of claim 1, said single base unit comprising:
 - a fuel source to provide a heating fuel to said first attachment unit; and
 - an affixing device to attach said fuel source container to said single base unit.
4. (currently amended): The apparatus of claim 1, said single base unit comprising:

a water reservoir configured to hold a prescribed volume of water;

a ~~sump~~ pump that pumps said water from said water reservoir to at least one drip source positioned at an upper edge of said single base unit; and

at least one evaporative cooling medium, positioned within a frame of said single base unit, that receives said water from said drip source, wherein said ambient air is evaporatively cooled at said at least one evaporative cooling medium, and said second attachment unit directs said cooled output.

5. (original): The apparatus of claim 1, said first attachment unit comprising:

a burner, positioned in a heater box, that receives and burns fuel to heat said base unit output; and

a register that permits outward flow of said heated output while restricting physical access to said first attachment unit.

6. (original): The apparatus of claim 5, further comprising a spark arrestor that prevents ignited debris produced by said burner from exiting said apparatus with said heated output.

7. (currently amended): The apparatus of claim 1, said first attachment unit comprising:

a control system comprising an ignition module and a flame sensor module, connected to an igniter unit, that monitors at least one of: (1) a differential pressure sensor, (2) an over-temperature ~~pressure~~ sensor and (3) a flame sensor to control a main control valve; and

| a blower, and a differential pressure control configured to control operation of ~~a~~-said
blower in said single base unit.

8. (original): The apparatus of claim 1, further comprising:

an adjustable flow valve that allows a user to set a heat level in a prescribed range; and

a maximum flow valve that limits said heated output from exceeding a prescribed level.

| 9. (currently amended): The apparatus of claim 1, wherein a ~~prescribed range~~ heat output
level of said heated output range is 75,000 BTU/hour to 200,000 BTU/hour, and a maximum
level of said heated output airflow is 200,000 BTU/hour.

10. (original): The apparatus of claim 1, wherein the apparatus is stationary.

11. (original): The apparatus of claim 1, further comprising wheels that allow movement
of said apparatus.

12. (original): The apparatus of claim 1, wherein said apparatus can be converted to a
heating mode by connecting a fuel supply to said single base unit and affixing said first
attachment unit to said single base unit.

13. (canceled).

14. (currently amended): The apparatus of claim 1, wherein a snout is attached to receive said output of said single base unit, said second attachment unit is affixed to one of said single base unit and said snout, in order to convert said apparatus to an evaporating cooling mode, and a power supply is attached to a ~~sump-pump~~ that pumps a water supply through said single base unit.

15. (original): The apparatus of claim 2, wherein at least one first pulley is engaged to operate said blower at a first speed, and at least one second pulley is engaged to operate said blower at a second speed.

16. (original): The apparatus of claim 15, wherein said at least one first pulley and said at least one second pulley are positioned on a double pulley device attached to said blower and said motor, a first belt is configured to be attached to said at least one first pulley and a second belt is configured to be attached to said at least one second pulley.

17. (currently amended): The apparatus of claim 1, further comprising a switch that is attached to said first attachment unit in a heating mode and to a ~~sump-pump~~ in said single base unit in an evaporative cooling mode.

18. (original): The apparatus of claim 3, wherein said fuel source is one of liquid propane and natural gas.

19. (currently amended): ~~A means~~ An apparatus for adjusting ambient air temperature, comprising:

a single base means for receiving an input airflow at said ambient air temperature and generating a base unit output airflow;

a first attachment means for receiving said base unit output and generating a heated output airflow, attachable to said single base ~~unit~~ means; and

a second attachment means for receiving said base unit output airflow and outputting ~~a~~ an evaporatively cooled output airflow, attachable to said single base ~~unit~~ means.

20. (withdrawn): A method of converting an apparatus to a cooling unit from a heating unit, comprising:

- (a) removing a modular heating shell;
- (b) electrically disconnecting a heater from said apparatus;
- (c) removing a modular heating attachment including said heater from said apparatus;
- (d) attaching a cooling attachment to said apparatus; and
- (e) electrically connecting a cooler to said apparatus.

21. (withdrawn): The method of claim 20, wherein at said (d), a cooling speed of a blower is set to be greater than a heating speed of said blower.

22. (withdrawn): The method of claim 20, wherein said (b) comprises electrically disconnecting an igniter and at least one safety controller from said apparatus.

23. (withdrawn): The method of claim 20, wherein said (c) comprises removing a heater box and a fuel supply from said apparatus.

24. (withdrawn): A method of converting an apparatus to a heating unit from a cooling unit, comprising:

- (a) removing a cooling attachment from said apparatus;
- (b) attaching a fuel source to said apparatus;
- (c) attaching a modular heating attachment to said apparatus; and
- (d) electrically connecting a heater to said apparatus.

25. (withdrawn): The method of claim 24, wherein at said (c), a heating speed of a blower is set to be greater than a cooling speed of said blower.

26. (withdrawn): The method of claim 24, wherein said (d) comprises electrically connecting an igniter and at least one safety controller to said apparatus.

27. (currently amended): An apparatus for adjusting ambient air temperature, comprising:

a single base unit, configured to receive an input airflow at said ambient air temperature and generate a base unit output airflow; and

~~an~~ attachment units, attachable to said single base unit and configured to receive said base unit output airflow and ~~one of~~ generate one of a heated output airflow and ~~output a~~ an evaporatively cooled output airflow generated in the single base unit, respectively.

28. (currently amended): The apparatus of claim 27, said single base unit comprising:

a blower that operates in accordance with a motor, wherein at least one first pulley is engaged to operate said blower at a first speed, and at least one second pulley is engaged to operate said blower at a second speed;

a detachable fuel source to provide a heating fuel to said attachment unit;

a water reservoir configured to hold a prescribed volume of water;

a ~~sump pump~~ that pumps said water from said water reservoir to at least one drip source positioned at an upper edge of said single base unit; and

at least one evaporative cooling medium, positioned within a frame of said single base unit, that receives said water from said drip source, wherein said ambient air is evaporatively

cooled at said at least one evaporative cooling medium, and said attachment unit directs said cooled output.

29. (original): The apparatus of claim 27, said attachment unit comprising:

a burner, positioned in a heater box, that receives and burns fuel to heat said base unit output; and

a register that permits outward flow of said heated output while restricting physical access to said first attachment unit.

30. (currently amended): The apparatus of claim 27, wherein a power supply is ~~switchably~~ interchangeably provided to one of:

an igniter and at least one control circuit in said attachment unit; and

~~a sump pump~~ that pumps a water supply through said single base unit.